Compiled byPrint DataAscani A.19/04/16

POWER SUPPLY SINGLE OUTPUT 5 W:

MAIN FEATURES

• Wide input voltage range

• Energy saving due to high efficiency and low standby power

• same footprint as EI30 transformer

ELECTRICAL SPECIFICATION

Input voltage range: 95 to 265 VAC
Input frequency range: 50 to 60 Hz
Output voltage accuracy (full load): ± 4%
Line output voltage variation: ± 0.3%
Load output voltage variation: ± 0.5%
No load input power: < 200 mW

SAFETY

Class II – reinforced insulation

Input/Output isolation test voltage: 4000VAC

Input protection: fuse resistor

Fully integrated auto-restart for short circuit

Operating temperature: -25 to Ta °C

STANDARDS

Safety: EN60950, EN61558


EMC: EN61000-6-3 (emission), EN61000-6-1 (immunity)

PART	OUTPUT	OUTPUT	OUTPUT	EFFICIENCY	Ta [°C]
NUMBER	VOLTAGE	CURRENT	POWER [W]		
	[VDC]	[mA]			
9541A001	12	420	5	> 0.7	+ 50
9541A001	12	420	5	> 0.7	+ 70*
9541A002	5	900	4.5	> 0.65	+50
9541A003	9	550	5	> 0.7	+50
9541A004	10.5	380	4	> 0.7	+60
	7	100			
9541A005	15	320	5	>0.7	+50
9541A006					

^{*}this Ta is available only with input voltage 230VAC±10%


Note: the value on the table are preliminary and could be changed.


ATTENTION: All the information shown on this specification is strictly confidential; in case of distribution without authorization from the manufacturer, penalties should be made.





Compiled by	Print Data		
Ascani A.	19/04/16		


DIMENSION AND PINOUT FOR CODE 9541A001, 9541A002, 9541A003, 9541A005












Compiled by	Print Data		
Ascani A.	19/04/16		

DIMENSION AND PINOUT FOR CODE 9541A004



DIMENSION AND PINOUT FOR CODE 9541A006

